

# **SNAKEBITE XQ**

## **BLAST NOZZLE**



### **DESCRIPTION**

The SnakeBite XQ blast nozzle is designed to reduce noise and nozzle thrust by modifying the jet stream exiting the blast nozzle, the SnakeBite XQ delivers up to 16dBA noise reduction and 45% lower nozzle thrust.

### **APPLICATIONS**

Ideal for blasting in noise sensitive areas and reducing operator fatigue to improve quality of life.

### **FEATURES**

- Improved blast nozzle geometry.
- New technology quick-connect nozzle silencer.
- Durable and lightweight Silicon Nitride Nozzle and Silencer liners.
- Slimline ergonomic nozzle jacket.
- Standard contractor nozzle inlet thread.
- Robust anodized aluminum nozzle jacket, including a nozzle exit bump guard.

### **BENEFITS**

- Increased ability to comply with employee noise exposure regulations
- Lower risk of operator and bystander hearing related injuries.
- Reduced noise impact on noise sensitive areas
- Reduced operator fatigue, over the shift and on an ongoing basis enabling high cleaning rates to be achieved throughout the shift.
- Reduced risk of worker manual handling related injury and injury caused by loss of operator nozzle control.

PART NUMBERS	
BNSBXQ6-1	SnakeBite XQ #6 High Productivity Silenced Blast nozzle, 3/8" Orifice, Contractor Thread
BNSBXQ7-1	SnakeBite XQ #7 High Productivity Silenced Blast nozzle, 7/16" Orifice, Contractor Thread
BNSBXQ8-1	SnakeBite XQ #8 High Productivity Silenced Blast nozzle, 1/2" Orifice, Contractor Thread

SPECIFICATIONS				
Nozzle Jacket Material	Anodized Aluminum			
Nozzle Liner Material	Silicon Nitride			
Nozzle Inlet Thread	Contractor			
Nozzle Size	Minimum air hose size	Minimum blast hose size	Weight (with silencer)	Length (with silencer)
No. 6 {3/8}	40 mm {1-1/2" }	32 mm {1-1/4"}	1.15 kg {2.52 lb}	336 mm {13.2 in}
No. 7 {7/16}	50 mm {2"}	32 mm {1-1/4"}	1.25 kg {2.75 lb}	385 mm {15.2 in}
No. 8 {1/2}	50 mm {2"}	40 mm {1-1/2"}	1.34 kg {2.94 lb}	435 mm {17.1 in}